



Information Sheet



Innovation™ Angle Port Splitters

Innovative splitters with the world's first angle port design!

Undoubtedly, this truly innovative, patented Angle Port Splitter designed by Gale Corporation is every technician's dream! This super-slim body can be installed in almost any termination closure allowing incredibly easy access to each port whether attaching or disconnecting a cable. The Angle Port Splitter has the most accessible ports of any splitter available!



FEATURES

- 25% improved circuit performance over our competitors' splitters
- 360° seizing pins on all ports
- SMT components on internal PCB
- 6kV surge withstand
- Premium Intermodulation distortion & second harmonics performance
- Soldered back plate
- Easily identified color-coded port labels
- Heavy duty cast zinc case with nickel plating, soldered together for -130dB RFI
- Unequaled forward & reverse insertion loss specifications
- Integrated ground block & mounting brackets

Part #:	Price:
AP2	\$3.29
AP3	\$4.49
AP4	\$5.29



Gale Corporation

P.O. Box 417280 Sacramento, CA 95841 | 888.566.5728 | info@galecorp.com | www.galecorp.com

© 2008 Gale Corporation | Pocket Toner is a registered trademark of Gale Corporation | Pocket Toner® -- Protected by U.S. Patent 6,437,580 | Pocket Toner® Adapters -- Protected by U.S. Patent 7,375,533



Angle Port Splitter Specifications

Model Number		AP2	AP3	AP4
Insertion Loss (Out)	Frequency (MHz)	Maximum (dB)		
	5-15	3.4	5.2	6.7
	15-40	3.3	5.2	6.5
	40-300	3.5	5.4	6.6
	300-500	3.5	5.6	6.8
	500-750	3.7	6	7.3
	750-1000	3.8	6.5	7.5

Isolation	Frequency (MHz)	Minimum (dB)		
	5-15	27.0	30.0	30.0
	15-40	40.0	40.0	40.0
	40-300	30.0	30.0	30.0
	300-500	24.0	25.0	25.0
	500-750	23.0	23.0	23.0
	750-1000	21.0	21.0	21.0

Return Loss (In)	Frequency (MHz)	Minimum (dB)		
	5-15	23.0	25.0	22.0
	15-40	25.0	28.0	23.0
	40-300	25.0	25.0	24.0
	300-500	25.0	24.0	25.0
	500-750	22.0	23.0	22.0
	750-1000	21.0	22.0	21.0

Return Loss (Out)	Frequency (MHz)	Minimum (dB)		
	5-15	25.0	25.0	23.0
	15-40	30.0	27.0	25.0
	40-300	30.0	25.0	30.0
	300-500	25.0	24.0	25.0
	500-750	23.0	23.0	23.0
	750-1000	21.0	22.0	21.0

RFI Isolation	Frequency (MHz)	Minimum (dB)		
	5-1000	130	130	130

Gale Corporation

P.O. Box 417280 Sacramento, CA 95841 | 888.566.5728 | info@galecorp.com | www.galecorp.com

© 2008 Gale Corporation | Pocket Toner is a registered trademark of Gale Corporation | Pocket Toner® -- Protected by U.S. Patent 6,437,580 | Pocket Toner® Adapters -- Protected by U.S. Patent 7,375,533